

NPGL-HM11D

NPGL-HM111D

NPGL-HMD111D

Input: 4 ~ 20 mA


Output: 4 ~ 20 mA

single input, single output

single input, double output

double input, double output


This isolator converts the current or voltage signals to current or voltage signals. It allows transmission of HART communication signals. The input, output, and power supply are galvanically isolated from each other.



Technical data	
Power supply:	18 V DC~32 V DC (Reverse power protection)
Power dissipation:	≤ 1.3 W (24V DC, single input single output) ≤ 1.8 W (24V DC, single input double output) ≤ 2.5 W (24V DC, double input double output)
Input signal:	Current: 0/4 ~ 20mA; 0 ~ 10mA Voltage: 0/1 ~ 5V; 0 ~ 10V
Input resistance:	Current: approx. 50 Ω Voltage: ≥ 1MΩ
Available voltage:	open-circuit voltage: ≤ 27 V voltage: ≥ 22 V at 20 mA
Output signal:	Sink mode: 4 ~ 20mA Current: 0/4 ~ 20mA; 0 ~ 10mA Voltage: 0/1 ~ 5V; 0 ~ 10V
Load resistance:	Sink mode: $R_L \leq [(U-3)/0.02]\Omega$; U: Loop power supply 0/4 ~ 20mA: $R_L \leq 450\Omega$; 0 ~ 10mA: $R_L \leq 900\Omega$ 0/1 ~ 5V: $R_L \geq 1M\Omega$; 0 ~ 10V: $R_L \geq 2M\Omega$
Accuracy:	± 0.1%F.S.
Temperature drift:	0.005%F.S./°C
Response time:	≤ 2ms
Electromagnetic compatibility:	IEC 61326-3-1
Dielectric strength:	≥ 1500 V AC (Input/Output) ≥ 500 V AC (Power supply/Output)
Insulation resistance:	≥ 100 MΩ (Input /Output/Power supply)
Operation temperature:	-20°C ~ +60°C
Storage temperature:	-40°C ~ +80°C
Dimension:	15.8 mm (W) × 121.6 mm (H) × 104.8 mm (D)

Model rules						Description
NPWD-HM		☐	☐	☐	☐	Isolator
Channel						Single as default
	D					Double channel
Input	1					4~20mA
	2					1~5V
	3					0~10mA
	4					0~5V
	5					0~10V
	6					0~20mA
Output1	1					4~20mA
	1S					Output sink mode: 4~20mA
	2					1~5V
	3					0~10mA
	4					0~5V
	5					0~10V
Output2	6					0~20mA
						None as default
	1					4~20mA
	1S					Output sink mode: 4~20mA
	2					1~5V
	3					0~10mA
Power supply	4					0~5V
	5					0~10V
	6					0~20mA
	D					24V DC

Wiring diagram



24V DC, double current input, double source current output

24V DC, double current input, double sink current output

24V DC, single voltage input, double current / voltage output